

ESTIMATION DPR							
<b>State</b>	Odisha	<b>District</b>	Kandhamal	<b>Block</b>	Baliguda	<b>Gram Panchayat</b>	Battaguda

<b>Work Code</b>	OD/359/3422/118868/416730/00050325 (Improvement of Rural Haat at Battaguda GP)
<b>Project Category</b>	Other Infrastructure

<b>Financial Year</b>	2025-26	<b>Execution Level</b>	PS
<b>Executing Agency</b>	Panchayat Samiti, Baliguda	<b>Proposal Date</b>	-
<b>Date of Commencement</b>	17-03-2026	<b>Date of Completion</b>	-
<b>Scheme Name</b>	5th SFC Grant in Aid	<b>Scheme Component Name</b>	Maintenance of Capital Assets
<b>Project Sub-Category</b>	Rural Haat	<b>Project Type</b>	New Work
<b>Name of Executant</b>	DURGA PRASAD ACHARY		

### Administrative Approval Details

<b>Approval No.</b>	OD/359/3422/118868/416730/00050325/AS
---------------------	---------------------------------------

### Technical Sanction Details

<b>Technical Sanction No.</b>	OD/359/3422/118868/416730/00050325/TS
<b>Fund Sanction No.</b>	33742
<b>Fund Sanction Amount (in Rs.)</b>	550000

### MATERIAL STATEMENT

SI.No.	Activity Name/Material	Qty/unit (B=Analysis Basic Qty/Header Unit)	Quantity (Meaurement Qty)	Unit
1	<b>Earth Work (AR0102aa) :.Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift -</b> Earth work in hard soil or gravelly soil foundation & plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge	-	<b>15.8007744</b>	Cum

2	<b>Earth Work (AR0115)</b> :.Filling foundation and plinth with sand well watered and rammed - Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T & P required for the work etc. complete and as per direction of Engineer-in charge.	-	<b>50.120736</b>	Cum
i)	<b>BRM029</b> : Sand for filling and road blinding	1	50.120736	1 Cum
3	<b>Concrete (AR0303)</b> :.Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal - Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&P required for the work etc. complete and as per direction of Engineer-in charge.	-	<b>76.45536</b>	Cum
i)	<b>BRM340</b> : Cement	2.29	175.0827744	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.48	36.6985728	1 Cum
iii)	<b>BRM044</b> : Granite Stone broken metal 40mm. size (Crusher broken)	0.96	73.3971456	1 Cum.

4	<p><b>Masonry Brick Work (AR0602d) :.C.B. Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:4) in foundation and plinth</b>  - Brickwork with C.B. Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:4) in foundation and plinth having crushing strength not less than 75.00 Kg/cm<sup>2</sup> with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&amp;P required for the work, etc. complete and as per direction of Engineer-in-charge.</p>	-	5.17064768	Cum
i)	<p><b>BRM001</b> : Well burnt clamp burnt bricks (25 Cm. x 12Cm. x 8Cm.) having crushing strength not less than 35 Kg./Cm<sup>2</sup> with dimensional tolerance ± 8 percent.</p>	350	1809.726688	1000 Nos
ii)	<p><b>BRM340</b> : Cement</p>	1	5.17064768	1 Qntl.
iii)	<p><b>BRM028</b> : Screened and washed sharp sand for mortar</p>	0.28	1.4477813504	1 Cum
5	<p><b>Plastering (AR1008) :.20mm thick cement Plaster in CM (1:6) over brick work in inside.</b> - 20mm thick cement Plaster in CM (1:6) for stone work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T &amp; P required for the work etc comp.and as per direction of Engineer-in-charge.</p>	-	24.247683	Sqm
i)	<p><b>BRM340</b> : Cement</p>	0.057	1.382117931	1 Qntl.
ii)	<p><b>BRM028</b> : Screened and washed sharp sand for mortar</p>	0.021	0.509201343	1 Cum

6	<b>Flooring (AR0802i)</b> :.2.5 cm thick A.S. <b>flooring in C.C (1:2:4)</b> <b>with 12 mm size HG</b> <b>crusher broken chips</b> - 2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG crusher broken chips including punning incl. cost, conveyance & royalty of materials as per direction of Engineer-in-charge.	-	<b>98.105568</b>	Sqm
i)	<b>BRM340</b> : Cement	0.0858	8.4174577344	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.012	1.177266816	1 Cum
iii)	<b>BRM056</b> : Granite Stone broken chips 12mm. size (Minimum 65% by Wt. Passing through 13.2mm sieve & retained on 9.50mm sieve but whole should pass through 19mm sieve) (Crusher broken)	0.023	2.256428064	1 Cum.

SI.No.	Material Name	Qty	Unit	Rate	Amount
1	<b>BRM029</b>	50.120736	1 Cum	541.31	27130.85560416
2	<b>BRM340</b>	190.0529977454	1 Qntl.	626.687	119103.74299807
3	<b>BRM028</b>	39.8328223094	1 Cum	548.19	21835.95486179
4	<b>BRM044</b>	73.3971456	1 Cum.	1531.66	112419.4720297
5	<b>BRM001</b>	1809.726688	1000 Nos	5.25865	9516.7192478512
6	<b>BRM056</b>	2.256428064	1 Cum.	1933.03	4361.7431405539

**Total: 294368.48788212**