

ESTIMATION DPR							
State	Odisha	District	Mayurbhanj	Block	Tiring	Gram Panchayat	Lupung

Work Code	OD/365/3511/120402/387467/00049371 (DEVELOPMENT OF RURAL HAAT AT LUPUNG)
Project Category	Building

Financial Year	2025-26	Execution Level	PS
Executing Agency	Panchayat Samiti, Tiring	Proposal Date	-
Date of Commencement	16-01-2026	Date of Completion	-
Scheme Name	5th SFC Grant in Aid	Scheme Component Name	Development of Rural Haat
Project Sub-Category	Market Complex	Project Type	Upgradation or Improvement
Name of Executant	PURUSOTTAM NAHAK		

Administrative Approval Details

Approval No.	OD/365/3511/120402/387467/00049371/AS
---------------------	---------------------------------------

Technical Sanction Details

Technical Sanction No.	OD/365/3511/120402/387467/00049371/TS
Fund Sanction No.	31804
Fund Sanction Amount (in Rs.)	1000000

MATERIAL STATEMENT

SI.No.	Activity Name/Material	Qty/unit (B=Analysis Basic Qty/Header Unit)	Quantity (Meaurement Qty)	Unit
1	Earth Work (AR0102aa) :.Earth work in hard soil or gravelly soil foundation & plinth within 50m. Initial lead and 1.5m initial lift - Earth work in hard soil or gravelly soil foundation & plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge	-	38.454	Cum

2	Earth Work (AR0115) :.Filling foundation and plinth with sand well watered and rammed - Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T & P required for the work etc. complete and as per direction of Engineer-in charge.	-	34.758	Cum
i)	BRM029 : Sand for filling and road blinding	1	34.758	1 Cum
3	Concrete (AR0303) :.Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal - Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&P required for the work etc. complete and as per direction of Engineer-in charge.	-	18.894	Cum
i)	BRM340 : Cement	2.29	43.26726	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.48	9.06912	1 Cum
iii)	BRM044 : Granite Stone broken metal 40mm. size (Crusher broken)	0.96	18.13824	1 Cum.

4	R.C.C. Work (AR0404A) :.Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips - Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. complete and as per direction of Engineer-in charge. (excluding centring and shuttering)	-	41.624	Cum
i)	BRM340 : Cement	3.4733	144.5726392	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.45	18.7308	1 Cum
iii)	BRM060 : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)	0.36	14.98464	1 Cum.
iv)	BRM052 : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)	0.54	22.47696	1 Cum.

5	R.C.C. Work (AR0410c) :R.C.C. foundation , plinth band and footings bases of columns mass concrete precast slabs etc - Rigid and smooth centring and shuttering for R.C.C. works including false works and dismantling them after casting including cost of materials complete in ground floor R.C.C. foundation, plinth band and footings bases of columns mass concrete precast slabs, etc	-	53.1	Sqm
i)	BRM104 : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.00267	0.141777	1Cum.
ii)	BRM092 : Non-sal bullahs 75mm. mean dia of any length.	0.126	6.6906	1Mtr.
6	R.C.C. Work (AR0410d) :Rigid and smooth centering and shuttering for R.C.C. works including false works and dismantling them after casting - Rigid and smooth centring and shuttering for R.C.C. works including false works and dismantling them after casting including cost of materials complete in ground floor R.C.C. beams, column, girder and bressmer, etc. Data for 4.2sqm	-	102.75	Sqm
i)	BRM084 : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.	0.55238095238095	56.757142857143	1Mtr
ii)	BRM104 : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.0051904761904762	0.53332142857143	1Cum.

7	<p>R.C.C. Work (AR0410a) :.Centring & Shuttering for R.C.C. floor and roof slabs, landings,balconies, projecting sun shades and chajjas - Rigid and smooth centring and shuttering for R.C.C. works including false works and dismantling them after casting including cost of materials complete in ground floor R.C.C. floor and roof slabs, landings, balconies, projecting sun shades and chajjas up to 4.3m height</p>	-	122.06	Sqm
i)	<p>BRM084 : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.</p>	0.622222222222222	75.9484444444444	1Mtr
ii)	<p>BRM104 : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)</p>	0.005022222222222	0.613012444444444	1Cum.
8	<p>Masonry Brick Work (AR0603b) :.Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in foundation and plinth - Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in foundation and plinth having crushing strength not less than 75.00 Kg/cm² with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&P required for the work, etc. complete and as per direction of Engineer-in-charge.</p>	-	7.8	Cum
i)	<p>BRM340 : Cement</p>	0.672	5.2416	1 Qntl.
ii)	<p>BRM028 : Screened and washed sharp sand for mortar</p>	0.28	2.184	1 Cum

iii)	BRM005 : Fly ash bricks of 25 Cm. x 12 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm2 with dimensional tolerance \pm 2 %	350	2730	1000 Nos
9	Masonry Brick Work (AR0603bi) :Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure - Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure having crushing strength not less than 75.00 Kg/cm2 with dimensional tolerance \pm 8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&P required for the work, etc. complete and as per direction of Engineer-in-charge.	-	2.5	Cum
i)	BRMMR0025 : SCAFFOLDING CHARGES FOR BRICK MASONRY WORK	1	2.5	1 Cum
ii)	BRM340 : Cement	0.672	1.68	1 Qntl.
iii)	BRM028 : Screened and washed sharp sand for mortar	0.28	0.7	1 Cum
iv)	BRM005 : Fly ash bricks of 25 Cm. x 12 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm2 with dimensional tolerance \pm 2 %	350	875	1000 Nos

10	Flooring (AR0802i) :.2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG crusher broken chips - 2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG crusher broken chips including punning incl. cost, conveyance & royalty of materials as per direction of Engineer-in-charge.	-	96.75	Sqm
i)	BRM340 : Cement	0.0858	8.30115	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.012	1.161	1 Cum
iii)	BRM056 : Granite Stone broken chips 12mm. size (Minimum 65% by Wt. Passing through 13.2mm sieve & retained on 9.50mm sieve but whole should pass through 19mm sieve) (Crusher broken)	0.023	2.22525	1 Cum.
11	Plastering (AR1027) :.6mm thick cement Plaster in CM (1:4) over R.C.C. surfaces including chipping (Inside) - 6mm thick cement Plaster in CM (1:4) over R.C.C. surfaces in inside including chipping with proper level and line, curing for the proper period with cost conveyance, royalty, taxes of all materials, labor, and T & P required for the work, etc comp. and as per the direction of the Engineer-in-charge.	-	207.74	Sqm
i)	BRM340 : Cement	0.0372	7.727928	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.0075	1.55805	1 Cum

12	Plastering (AR1014) :.16mm thick cement Plaster in CM (1:6) over brick work in inside. - 16mm thick cement Plaster in CM (1:6) over brick work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp.and as per direction of Engineer-in-charge.	-	21.5	Sqm
i)	BRM340 : Cement	0.043	0.9245	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.018	0.387	1 Cum
13	R.C.C. Work (AR0409) :.Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position - Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position including cost of binding wire 18 to 20 gauge with cost of steel rod and as per drawing, design, and direction of Engineer-in-charge.	-	25	Qntl
i)	BRM162 : Binding Wire.	0.8	20	1 Kg.
ii)	BRM341 : Steel	1.05	26.25	1 Qntl.

14	Plastering (AR1017) :.20mm thick cement Plaster in CM (1:4) over masonry work in inside. - 20mm thick cement Plaster in CM (1:4) over stone work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp.and as per direction of Engineer-in-charge.	-	116.6	Sqm
i)	BRM340 : Cement	0.0744	8.67504	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.021	2.4486	1 Cum
15	Painting(AR0921k) :.Finishing wall One Coat with distemper of approved shades on old work (Inside)(For repair and maintenance). - Finishing wall One Coat with distemper of approved shades on old work to give an even shade including all costs of labor, Paint and Brushes required for the work, etc. complete and as per direction of the Engineer-in-charge.(Inside)(For repair and maintenance).	-	181.1	Sqm
i)	BRM142 : Distemper	0.166	30.0626	1 Kg.

16	Painting(AR0918g) :.Finishing wall with two coats weather coat paint of approved shade including one coat of oil bound primer in the outer surface of old work .(Outside) - Finishing wall with two coats weather coat paint of approved shade including one coat of oil bound primer in the outer surface of old work to give an even shade including all costs of labour, Paint, Brushes, and putty required for the work, etc. complete and as per direction of Engineer-in-charge. (Outside)	-	48.1	Sqm
i)	BRM255 : Weather Coat (I.S.I.)	0.125	6.0125	1 Ltr
ii)	BRM252 : Wall cement primer (I.S.I.) Oil bound	0.084	4.0404	1 Ltr

SI.No.	Material Name	Qty	Unit	Rate	Amount
1	BRM029	34.758	1 Cum	466.64	16219.47312
2	BRM340	220.3901172	1 Qntl.	650.622	143390.6588329
3	BRM028	36.23857	1 Cum	473.06	17143.0179242
4	BRM044	18.13824	1 Cum.	1401.46	25420.0178304
5	BRM060	14.98464	1 Cum.	1786.21	26765.7138144
6	BRM052	22.47696	1 Cum.	1788.5	40200.04296
7	BRM104	1.2881108730159	1Cum.	58620.646	75509.891495814
8	BRM092	6.6906	1Mtr.	276.666	1851.0615396
9	BRM084	132.70558730159	1Mtr	297.726	39509.903684952
10	BRM005	3605	1000 Nos	6.60035	23794.26175
11	BRMMR0025	2.5	1 Cum	33	82.5
12	BRM056	2.22525	1 Cum.	1802.83	4011.7474575
13	BRM162	20	1 Kg.	90	1800
14	BRM341	26.25	1 Qntl.	6225.277	163413.52125
15	BRM142	30.0626	1 Kg.	70.52622	2120.201541372
16	BRM255	6.0125	1 Ltr	195.21622	1173.73752275
17	BRM252	4.0404	1 Ltr	125.92622	508.792299288
Total: 582914.54302318					